

1-4 Nakadori Mizushima Kurashiki City, Okayama Pref. 712-8502 Japan TEL: 81-86-440-0821 FAX: 81-86-440-0819

DECLARATION OF PERFORMANCE

NO. 1

- 1. Unique identification code of the product type: BarChip 48
- 2. Type, batch or serial number or any other element allow identification of the construction product as required pursuant to Article 11(4): Each delivery of the product is identified by the name: BarChip 48 and by the batch number.
- 3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: Polymer fibres for structural uses in concrete mortar and grout.
- **4.** Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Hagihara Industries 1-4 Nakadori Mizushima Kurashiki Okayama Pref. Japan

Tel: (81) 86 440 0821 Fax: (81) 86 440 0819

- **5.** Where applicable, name and contact address of the authorised representative whose mandate coves the tasks specified in Article 12(2):
- **6.** System or systems of assessment and verification of constancy of performance for the construction productions as set out in Annex V: **System 1**
- **7.** In case of the declaration of performance concerning a construction product covered by a harmonised standard:

SGS performed the

- Determination of the product type on the basis of type testing (including sampling)
- Initial inspection of the manufacturing plant and of the factory production control
- Continuous surveillance, assessment and evaluation of the factory production control

and issued a certificate of consistence of performance.



1-4 Nakadori Mizushima Kurashiki City, Okayama Pref. 712-8502 Japan TEL: 81-86-440-0821 FAX: 81-86-440-0819

TLL. 81-80-440-0821 FAX. 81-80-440-0819

8. Declared performance

Essential Characteristics	Performance	Harmonised Technical Specification
Class	II	EN 14889-2:2006
Length	48 mm	
Equivalent diameter	0.70 mm	
Tensile strength	640 N/mm²	
Modulus of elasticity	10 kN/mm²	
Melting point	165 – 170 °C	
Point of ignition	360 °C	
Effect on consistence of	9 s with 3 kg/m³	
concrete	(Reference concrete; 7 s)	
Effect on strength of	3 kg/m³ to obtain	
concrete	1.6 N/mm ² at CMOD-0.5 mm; and	
	1.6 N/mm ² at CMOD-3.5 mm	
Release of dangerous	No release of any dangerous	
substances	substances	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Name: Masataka Sasaki Function: Quality Assurance Manager

(Name and Function)

Place: 1-4 Nakadori Mizushima Kurashiki, Okayama Pref. Japan 712-8502

Date of issue: 28 August 2018

(Place and Date of Issue)

(Signature)